



Fujian Anyuan (Antai) Rubber Technology Co., Ltd
Shenzhen Mingpai Technology Co., Ltd

Titanium dioxide(Rutile)FR-767 Technical Instructions(TDS)

Active ingredients	TiO2	Other ingredients	
---------------------------	-------------	--------------------------	--

Product introduction

This product is a high-grade general-purpose rutile titanium dioxide produced by sulfuric acid method.
This product has good whiteness, good gloss, good brightness and stable color.
FR-767 products have small particle size, concentrated and uniform distribution,
which can obviously show blue background phase,high gloss, high covering power, high dispersibility and
coloring power.This product is widely used in EVA masterbatches, profiles, tubes and other plastic systems
and rubber systems, as well as exterior architectural coatings, industrial coatings, powder coatings field.

Product index

Items	appearance	TiO2 content	Rutile content	Achromatic power	Water Suspension Emulsions
Unit	White powder	%	%	Reynolds Index	PH
Index	——	93.00	98	1800.0	6.5-8.5

Usage method

Can be added directly in the refiner or opener
Can be used in sulfur vulcanization system, non-sulfur vulcanization and peroxide vulcanization
system.
Suggested usage:10phr-20phr
Please add according to the application and actual requirements.

Package specification/ shelf life

25kg/ bag
Twelve months from the date of production. If the storage is expired, it can still be used after re inspection

Attention points

1. This product is not flammable	Flammability not flammable
2. Store away from strong acids and alkalis to prevent deterioration by dissolution	
3. Store in a ventilated and dry place	

Company Name	Fujian Anyuan Rubber Technology Co., Ltd		
Address	No. 22, Jiulongshan Industrial Zone, Hanjiang Town, Shishi City, Fujian		
Phone	0595-85151198	Website	www.fjayxj.com